

A UML profile for transforming GRAI Extended Actigrams into UML [★]

Reyes Grangel^{*} Anne-Françoise Cutting-Decelle^{**}
Jean-Pierre Bourey^{**}

^{*} *Grupo en Integración y Re-Ingeniería de Sistemas (IRIS), Dept. de
Llenguatges i Sistemes Informàtics, Universitat Jaume I, 12071
Castelló, Spain (e-mail: grangel@uji.es)*

^{**} *Laboratoire de Génie Industriel de Lille, Ecole Centrale de Lille,
59561 Villeneuve d'Ascq Cedex, France (e-mails:
anne-francoise.cutting-decelle@ec-lille.fr, jean-pierre.bourey@ec-lille.fr)*

Abstract: Interoperability is one of the main problems linked to the rapid evolution of Information and Communication Technologies (ICT), and to the need to set up quickly alliances among different kinds of enterprises based on cooperative information systems in order to benefit from market opportunities. Solving this problem at both the Enterprise Modelling level and the Business Process Modelling instead of the code level by using model-driven approaches is a promising proposal.

In this context, this paper mainly focuses on transformations of business process models at the Enterprise Modelling level. This kind of transformation is one component of a more general model-driven approach to solve business process integration problems or, more widely, interoperability problems. This describes a UML Profile definition to transform GRAI Extended Actigrams into UML Activity Diagrams, as a mechanism to avoid the semantic losses generated by transformations. The implementation of this Profile with the Atlas Transformation Language (ATL) is finally presented.

1. INTRODUCTION

Enterprises must tailor their functions and processes to improve their competitiveness and to take advantage of new market opportunities. Both Business Process and Enterprise Modelling methods have been successfully used by enterprises to integrate their information and manufacturing systems throughout the last few decades [Vernadat, 1996]. New problems, such as Business Process Integration or more widely Interoperability, arise in collaborative enterprises. Solving these problems not only at the code level but also at a higher level of abstraction (i.e. at the enterprise modelling) level is a great challenge. The two main problems we have to address at this level are, first, that the enterprises may use different formalisms to express their process models and, second, that the gap between business models and models used in the IT domain must be filled. For solving the first kind of problems, point to point model transformations can be developed for each couple of used formalisms. Another more effective way, is to use a neutral formalism, framework or architecture supporting integration [Anaya and Ortiz, 2005]. This last solution was presented for example in [Cuenca et al., 2006] where CIMOSA [Berio and Vernadat, 1999] was used as integration framework. This work focused more on the mapping of UML Use Cases or DFD models onto CIMOSA partial models to perform enterprise integration. For solving the second kind of problems, MDA-based approach [OMG,

2003] can be used. Within this kind of approach different levels of abstractions are defined from business level (enterprise level) down to code. The transition from one level to another is supported by transformations. The common point of these approaches is that they are both model- and transformation based for solving what can be called horizontal or vertical interoperability. In this context, the Task Group 2 (TG2) of the INTEROP NoE [INTEROP, 2007] has worked on models and transformations to be performed at the Computation Independent Model level from theoretical point of view. At this level the GRAI method [Doumeingts et al., 1993, Berio, 2003] has been chosen for capturing the enterprise models and UML as an interface between enterprise models and IT models. To ensure the feasibility of its proposal, TG2 worked on transformations from the Business Process Modelling point of view, i.e. from GRAI Extended Actigrams to UML Activity Diagrams [Bourey et al., 2006] and the results presented in this paper deal with the definition of a UML Profile and its use with a transformation language to perform a transformation without semantic loss.

The paper is organised as follows. Section 2 defines the context of the study. Section 3 gives an overview on model transformation concepts. In Section 4, the basic constructs of GRAI Extended Actigrams are presented and a first mapping with semantic losses is described and discussed. Then, a UML profile is defined in Section 5 and implemented within a transformation tool presented in Section 6. Finally, Section 7 outlines the main conclusions.

[★] This work was funded by the EC within the 6th FP, INTEROP NoE [INTEROP, 2007]. The authors were indebted to TG2. It was also partially supported by DPI2006-14708.

2. CONTEXT OF THE STUDY

Enterprise Modelling is achieved through using Enterprise Modelling Languages. In this context, there are several formalisms and methodologies dealing with Enterprise Modelling, such as GRAI¹ [Doumeingts et al., 1993, Berio, 2003], CIMOSA [Berio and Vernadat, 1999], PERA [Williams, 1993], IDEF [IDEF, 2007], and so forth. The **GRAI Methodology** is a well-known Enterprise Modelling Methodology. One of the strengths of this Enterprise Modelling Methodology is that it takes into account both the decisional and the functional aspect together, as well as the informational and business process aspects. All these aspects are taken into account from both a general and a local point of view. **GRAI Extended Actigram** (noted 'GRAI EA' in the following) are dedicated to Business Process Modelling. However, one the main weaknesses of Enterprise Modelling Languages is the difficulty in establishing strong links between enterprise models and software development [Grangel et al., 2005]. This paper addresses one part of this issue and more precisely the Business Process Modelling aspects by defining a transformation of **GRAI Extended Actigram**.

On the other hand, **UML** [OMG, 2007], which has been successfully used to model and develop information systems in different domains, can also be useful in the context of Enterprise Modelling [Marshall, 2000, Eriksson and Penker, 2000]. It is the most widely known Object Management Group (OMG) specification, as an object-oriented modelling and specification language used to model applications in the context of Software Engineering. Numerous revisions have enabled UML to mature significantly to UML 2.1.1, which is the current OMG adopted specification [OMG, 2007]. For these reasons, UML is a good candidate to establish links between the context of Enterprise Modelling and Software Engineering, and therefore, to bridge the gap between these two contexts.

3. MODEL TRANSFORMATIONS

The objective is to transform a source model 'Ma' into a target model 'Mb'. One of the most commonly used techniques for model transformation is known as the 'MetaModel Approach' [OMG, 2003] based on the **Model Transformation Pattern** shown in Fig. 1. In this approach, the first step consists in defining source and target metamodels (resp. 'MMA' and 'MMb') defining the languages used for the model descriptions (resp. 'Ma' and 'Mb'). Each model conforms to its metamodel. Then a mapping ('Tab') between the metamodels is built. It consists in establishing correspondances between constructs of each metamodel. This mapping can be defined as a simple table showing the construct matching. For example in [Cuenca et al., 2006] a table for the mapping of UML use cases or DFD onto CIMOSA can be found. This kind of table can be used as specification to be implemented by using a more formal and executable language (like XSL, general programming languages or languages dedicated transformation such ATL [Jouault et al., 2006]). In this case the used language conforms to its metamodel 'MMt'. By using an executable language it is possible to




Fig. 1. Model Transformation Pattern from [Allilaire et al., 2006]




Fig. 2. GRAI Extended Actigram metamodel: structure perform the transformation 'Tab' from any input model 'Ma' conforming to 'MMA' to generate the corresponding target model 'Mb' conforming to 'MMb'.

In our study 'MMA' is the GRAI EA metamodel. It will be described in the following section. 'MMb' is the UML metamodel which is completely defined in [OMG, 2007]. A first mapping from 'MMA' to 'MMb' is presented in section 4.2. Since this mapping introduces semantic losses, the target UML metamodel is extended that means that the extension mechanism of UML is used to define a dedicated Profile presented in section 5.

4. FIRST TRANSFORMATION FROM GRAI EXTENDED ACTIGRAM TO UML ACTIVITY DIAGRAM

GRAI EA are one of the three main formalisms defined in the GRAI Methodology. It is used to model business processes and is an extension of IDEF0 Diagrams [IDEF, 2007]. The main concepts of GRAI EA and their relations are represented on the Metamodel shown in Fig. 2 and 3 and described more in detail hereafter. A more complete GRAI EA Metamodel description can be found in [Berio, 2003, Grangel et al., 2007].

4.1 GRAI Extended Actigram

A GRAI Extended Actigram is composed of:

- **Process:** set of extended activities that are logically inter-related and triggered by flows and eventually by using operators.
- **Activity:** this represents a transformation and a production (output flow). Due to the hierarchical structure of an Extended Actigram, an activity can be broken down into several activities. In this case, from here on, the activity will be called a 'Structured Activity'. An activity that has not been broken down will be called a 'Leaf Activity'.

¹ Graph with Results and Activities Interrelated




Fig. 3. GRAI Extended Actigram metamodel: flow connections




Fig. 4. Excerpt of a GRAI Extended Actigram

GRAI Extended Actigram	Condition	UML Activity Diagram
Extended Actigram Model		Model
Process		Activity
Activity	it is a structured Activity	Activity + CallBehaviourAction
	it is a non structured Activity	Action
Connector		ActivityParameterNode
LogicalOperator	Converging OR	MergeNode
	Converging AND	JoinNode
	Diverging OR	DecisionNode
	Diverging AND	ForkNode
Resource		ActivityParameterNode
Flow	not connected to a Resource or to a connector	ControlFlow
	connected to a Resource or to a connector	ObjectFlow

Fig. 5. Simple mapping of GRAI EA to UML AD

- **Resource:** human or material mean used by a process to support one or several activities.
- **Connector:** used to represent the origin or the destination of a flow when the origin or the destination is outside the current diagram. Possible roles are: *process connector*, *internal connector*, *external connector*.
- **Flow:** used to link *Activities*. A flow is directed and can be an *input*, *output*, *control* or *resource* of an activity. A flow can also be used to link *Connectors* to other diagram elements.
- **Logical Operator:** this represents a convergence or a divergence of multiple flows and their timing. There are three different kinds of process logical operators: *synchronous AND (sAND)*, *asynchronous AND (aAND)* and *OR*.

Fig. 4 shows an excerpt of a GRAI EA describing an order management process of a real case study.

4.2 First Mapping

Grangel et al. [2007] have proposed and implemented a first transformation from GRAI EA to **standard** UML AD using the basic UML constructs defined in [OMG, 2007]. This mapping is synthesised in Fig. 5. This table is made of three columns. The first one describes the source constructs of GRAI EA. The second one describes, when mentioned, the conditions to be checked out in order to select the corresponding target construct of UML AD described in the third column.

4.3 Application and Discussion

The implementation of a transformation in conformance to this first mapping of the GRAI EA to UML AD leads to some semantic losses which are:

- (1) **Connectors and Resources.** Since these two source constructs are mapped onto the same target elements, it is impossible to determine on the obtained model if the *ActivityParameterNode* is related to a resource or to a connector. Moreover, for this source construct, its type (internal, external, process) is not preserved.
- (2) **Synchronism features of AND operator.** This information is not preserved during the transformation of the source model.
- (3) **Type of incoming flows** of the obtained activities: it is impossible to determine if these flows are input, control or resource flows as they appear in the source model. The type of flow (product or information) is also lost. At last the type of GRAI Resources ('human' or 'material') is not preserved by the transformation.

All these semantic losses make it impossible to have a complete traceability between the source and the target model. It is also impossible to build up a reverse transformation from the obtained UML AD to a GRAI EA.

The question is then, how to preserve the semantics of the source model after the transformation? Two main approaches for solving this problem can be investigated. The first one consists in enriching the set of constructs of the target modelling language and then in keeping additional information in the target model. The second one consists in keeping the additional semantics 'outside' the target model, for example, by storing applied transformation rules into a log file. In this paper, only the first approach is investigated through the definition of a UML profile, which is presented in the next section.

5. UML PROFILE DEFINITION

A profile is a specific version of UML. Generally, a profile is first defined by means of a domain model which represents the new concepts and their relationships as well as a description of their semantics. Then the mapping of these new concepts onto UML constructs is defined through a set of extension elements applied to the UML basic constructs. Therefore a UML Profile can be considered as a lightweight extension mechanism that adapts a UML Metamodel [OMG, 2007] to one Specific Modelling Domain. A typical UML Profile is made up of stereotypes, tagged values and constraints [OMG, 2007]:

- **Stereotypes:** these are specialisations of the meta-class 'Class'; they define how an existing metaclass may be extended. Each stereotype may extend one or more metaclasses of the UML Metamodel.
- **Tagged Values:** these are properties of a stereotype and are standard metaattributes.
- **Constraints:** these are conditions or restrictions expressed in natural language text or, better, in a machine readable language such as OCL [OMG, 2006].




Fig. 6. Stereotypes extending UML ControlFlow and ObjectFlow

The profile definition presented in this section is only applies to the GRAI EA transformation. It is a part of a more general on-going work that aims at defining a complete specialisation of UML for bridging all the GRAI formalisms (Extended Actigram, Grids and Nets) with UML. Since the objective is both to transform GRAI EA and to define a UML profile, the starting domain model for the profile definition is the GRAI EA metamodel presented in Section 4.1. As mentioned, one of the main problems of model transformations is the loss of information. In this section, an approach based on the definition of a UML Profile called 'UML Profile for GEA2UAD' is presented.

5.1 Flows

GRAI defines four types of flows: Control Flow, Resource Flow, Input Flow and Output Flow. This definition of types of flow is given from an activity point of view. Another type of flow can be introduced. It deals with flows which establish connections between two operators or between one operator and one connector. This kind of flow will be named 'Intermediate Flow' in the following. To keep this distinction between different flow types, five main stereotypes are defined as illustrated in Fig. 6 and are called 'graiInputFlow', 'graiControlFlow' and 'graiResourceFlow', 'graiOutputFlow' and 'graiIntermediateFlow'. All these stereotypes are specialisations of the abstract stereotype 'graiFlow', which has been introduced to factorise the common property 'graiFlowNature' introduced to characterise the type of flow (information or product). The abstract stereotype 'graiFlow' is an extension of both UML ControlFlow and ObjectFlow because one GRAI Flow can be transformed either into a UML ControlFlow or ObjectFlow depending on the nature of the GRAI elements it links. Actually, the transformation result must conform to the UML Metamodel and especially to its connection rules: a UML ObjectNode is only connected to other nodes using an ObjectFlow. Therefore if a GRAI Flow connects a resource or a connector which are both mapped onto UML ActivityParameterNode (as explained in section 5.3) which is a specialisation of UML ObjectNodes, then the GRAI Flow must be transformed into a UML ObjectFlow. In the other case, GRAI Flow are transformed into a UML ControlFlow. Fig. 6 also shows the definition of the enumeration 'GraiFlowNatureType' containing two literals ('information' and 'product') used to type the property 'graiFlowNature'.




Fig. 7. Stereotypes extending UML JoinNode and ForkNode




Fig. 8. Stereotypes extending UML ActivityParameterNode

5.2 Synchronous and Asynchronous Operators

As illustrated in Fig. 7, UML JoinNode and ForkNode were extended using two different stereotypes: 'graiSynchronous' and 'graiAsynchronous'. The use of these stereotypes make it possible to keep in the obtained UML model information depending on the nature of the source GRAI Logical Operator (Synchronous or Asynchronous) [Berio, 2003].

5.3 Connectors and Resources

The third type of extension defined is related to the UML ActivityParameterNode Metaclass. ActivityParameterNodes are ObjectNodes at the beginning and the end of flows, they accept inputs to an activity and provide outputs. As illustrated in Fig. 8, four stereotypes are defined as extensions of ActivityParameterNodes: three of them correspond to each type of GRAI connector ('graiExternalConnector', 'graiInternalConnector' and 'graiProcessConnector') and the fourth deals with the mapping of GRAI resources. A property is added to the stereotype 'graiResource' in order to specify the type of resource ('material' or 'human').

5.4 Application

The proposed profile described in the previous sections is used to define a new mapping presented in Fig. 9. Compared to Fig. 5, two columns have been added on the left part. The first one defines the stereotypes to be used according to the source element and the condition. The second one gives the different values to be given to stereotype properties when needed.

6. IMPLEMENTATION WITH A MODEL TRANSFORMATION TOOL

In order to demonstrate the feasibility of the implementation of the proposal, this section shortly presents a Model Transformation Language. Then, the application of the defined UML Profile is described.

6.1 ATL Overview

Atlas Transformation Language (ATL) [Jouault et al., 2006] is a hybrid of declarative and imperative transformation languages based on OCL [OMG, 2006]. The preferred

GRAI	Condition	UML	Stereotype	Tagged Value
Extended Actigram		Model		
Process		Activity		
Activity	not a structured Activity	OpaqueAction		
	structured Activity	Activity +		
Connector		CallBehaviourAction		
	Process	ActivityParameterNode	graiProcess	
	Internal	ActivityParameterNode	graiInternal	
	External	ActivityParameterNode	graiExternal	
Resource		ActivityParameterNode	graiResource	Material / Human
Flow	Input Flow / Control Flow / Resource Flow / Output Flow / Intermediate Flow not connected to a Connector nor to a Resource	ControlFlow		Information / Product
	Input Flow / Control Flow / Resource Flow / Output Flow / Intermediate Flow connected to a Connector or to a Resource	ObjectFlow		Information / Product
LogicalOperator	Converging OR	MergeNode		
	Converging Synchronous AND	JoinNode		
	Converging Asynchronous AND		graiSynchronous	
	Diverging OR	DecisionNode		
	Diverging Synchronous AND	ForkNode		graiSynchronous

Fig. 9. Definition of a mapping using the proposed UML Profile

style of transformation writing is declarative, which means that mappings can be expressed rules. However, imperative constructs are provided so that some mappings too complex to be declaratively handled can still be specified inside rules or by means of helpers.

A **rule** describes the transformation from a source model to a target model by relating metamodels. It is introduced by the keyword 'rule' followed by the rule's name. In the **source pattern**, rules declare which element type of the source model has to be transformed. It consists of the keyword 'from', a source variable declaration and an optional precondition. This precondition is expressed using an OCL expression that restricts the rule triggering to elements of the source model that satisfy this precondition. A **first optional section** introduced by the keyword 'using' can be used to declare local variables. In the **target pattern**, rules declare element(s) of the target model the source pattern has to be transformed into. It may contain one or several target pattern elements. A target pattern element starts with the keyword 'to' and consists of a variable declaration and a sequence of bindings (assignments). The **second optional section** is the 'do' section. This section specifies a sequence of ATL imperative statements that will be executed once the initialisation of the target model elements generated by the rule has been completed. This section will be used below to apply stereotype to a target element. The general structure of a rule is shown in the following code.

```
rule <ruleName> {
  from <sourceVariable> : <sourceMetaModel>!<sourceElement>
    [(<precondition>)]
  [using <local variable declaration>]
  to <targetVariable> : <targetMetaModel>!<targetElement>
    (<assignments>)
  [do {<imperative statements>}]
} -- end of the rule
```

6.2 Applying UML Profiles

ATL makes it possible to use UML Profiles. The method to use profile with ATL is made up of four steps:

- (1) The first one consists in defining the profile with an UML tool.
- (2) In the second step, the profile is applied to the generated UML model. For example, in order to apply the profile called 'UML_Profile_for_GEA2UAD' to a target UML Model, the following statement must be




Fig. 10. UML Activity Diagram using the profile

added in the 'do' section of the rule creating the UML Model:

```
target_UmlModel.applyProfile(UML2!Profile.allInstances()->
  select(e | e.name = 'UML_Profile_for_GEA2UAD').first());
```

- (3) The third step consists in applying stereotypes to the elements of the UML target model for which we want to keep additional semantics coming from the source model. The 'applyStereotype' method is invoked on the target element with an instance of the metaclass 'Stereotype' as parameter. To get it, the 'getApplicableStereotype' method is invoked with the name of the stereotype to apply.
- (4) Finally, for target elements, tagged values of stereotyped UML model elements are set using the 'setValue' method. This method is invoked on a UML element through the use of three parameters: (1) the stereotype, (2) the name of the tagged value and (3) its value.

6.3 Discussion

To date, 19 ATL rules have been written to implement the complete mapping and Fig. 10 shows the result obtained after the transformation of the GRAI EA shown in Fig. 4. The defined UML Profile has been used and Fig. 10 shows especially the stereotypes used for Flows and ActivityParameterNodes. This graphical output was obtained after importing the generated model into a UML Modelling tool.

This experiment has shown how it was possible to define a UML profile to fill in the semantic gap between GRAI EA and UML AD and to implement the profile-based mapping using a transformation language. This approach which is not limited to GRAI EA makes it possible to establish a bridge between dedicated Enterprise Modelling Languages and UML. It can be used within a vertical MDA approach to link together CIM and PIM levels. This approach can also be used horizontally to transform enterprise models expressed using different formalisms into models using a unique language thus leading to an improved interoperability between the enterprise systems.

7. CONCLUSION

The first contribution of this paper is focused on the transformation from GRAI EA to UML AD, and particularly

on a specialisation of UML AD through a profile definition. This profile makes it possible to define a complete mapping without semantic losses between the two modelling languages used for business process modelling. That is the reason why this mapping is more adapted to solve horizontal interoperability problems at CIM level. The second contribution is related to the implementation of the defined mapping. A transformation language has been presented and used both to show how a profile can be implemented and to validate the mapping by experimentation. The study developed within the framework of the project tends to demonstrate the feasibility of an overall proposal for improving the interoperability and the cooperation in a Business Process Management context.

The profile discussed in the paper is a part of a more general UML specialisation dedicated to the transformation of all the GRAI formalisms into UML. Two other profiles are under development for the transformation of GRAI Grids and GRAI Nets used for decision making processes modelling. About interoperability problem solving, the main interest of this kind of transformations is, first, to bridge the gap between the business process modelling domain that uses specific methodologies such as GRAI, and the software development domain using UML. More generally, this proposal can be considered as a translation from one formalism to another one, and therefore, it can be used to achieve an horizontal interoperability between two enterprises that use two different business process modelling languages at the same level of abstraction.

REFERENCES

- F. Allilaire, J. Bézin, F. Jouault, and I. Kurtev. ATL - Eclipse Support for Model Transformation. In *Proceedings of the Eclipse Technology eXchange Workshop (eTX) at the ECOOP 2006 Conference, Nantes, France, 2006*.
- Victor Anaya and Angel Ortiz. How enterprise architectures can support integration. In *IHIS'05: Proceedings of the first international workshop on Interoperability of Heterogeneous Information Systems*, pages 25–30, New York, NY, USA, 2005. ACM. ISBN 1-59593-184-5. doi: <http://doi.acm.org/10.1145/1096967.1096973>.
- G. Berio. Project UEML, WP3, Deliverable D3.3, Requirements Analysis: initial core constructs and architecture, Annex2.2, GRAI metamodelling v2.5. Technical report, 2003. URL http://athena.troux.com/AKMii/WebComputas/TeamBlob.aspx?TeamPage=/Team/Repository/Projects/Project_249/Upload/Attachments/239_30_124__Annexes31.zip.
- G. Berio and F. B. Vernadat. New developments in enterprise modelling using CIMOSA. *Comput. Ind.*, 40 (2-3):99–114, 1999. ISSN 0166-3615.
- J-P. Bourey, R. Grangel, G. Doumeings, and A. Berre. INTEROP NoE: Deliverable DTG2.2: Report on Model Interoperability, 2006. URL <http://interop-noe.org/deliv/dtg22>.
- L. Cuenca, A. Ortiz, and F. Vernadat. From UML or DFD models to CIMOSA partial models and enterprise components. *International Journal of Computer Integrated Manufacturing*, 19(3):248–263, April-May 2006. doi: [doi: 10.1080/03081070500065841](https://doi.org/10.1080/03081070500065841). URL <http://www.tandf.co.uk/journals>.
- G. Doumeings, D. Chen, B. Vallespir, P. Fénié, and F. Marcotte. GIM (GRAI Integrated Methodology) and its Evolutions - a Methodology to Design and Specify Advanced Manufacturing Systems. In Hiroyuki Yoshikawa and Jan Goossenaerts, editors, *DIISM '93: Proceedings of the JSPE/IFIP TC5/WG5.3 Workshop on the Design of Information Infrastructure Systems for Manufacturing*, volume B-14 of *IFIP Transactions*, pages 101–120. North-Holland, 1993. ISBN 044481681X.
- H. Eriksson and M. Penker. *Business Modeling with UML: Business Patterns at Work*. J. Wiley, 2000.
- R. Grangel, R. Chalmeta, C. Campos, and Ò. Coltell. Enterprise Modelling, an overview focused on software generation. In H. Panetto, editor, *Interoperability of Enterprise Software and Applications Workshops of the INTEROP-ESA International Conference EI2N, WSI, ISIDI and IEHENA 2005*, pages 65–76. Hermes Science Publishing, 2005.
- R. Grangel, R. Ben Salem, J-P. Bourey, N. Daclin, and Y. Ducq. Transforming GRAI Extended Actigrams into UML Activity Diagrams: a First Step to Model Driven Interoperability. In Ricardo J. Gonçalves, Jörg Muller, Kai Mertins, and Martin Zelm, editors, *3rd International Conference on Interoperability for Enterprise Software and Applications, Enterprise Interoperability II, New Challenges and Approaches*, pages pp447–458. Springer, March 2007. ISBN 978-1-84628-857-9.
- IDEF. Integrated DEFinition Methods, 2007. URL <http://www.idef.com/>.
- INTEROP. Interoperability Research for Networked Enterprises Applications and Software NoE (IST-2003-508011), 2007. URL <http://www.interop-noe.org>.
- F. Jouault, F. Allilaire, J. Bézin, I. Kurtev, and P. Valduriez. ATL: a QVT-like transformation language. In Peri L. Tarr and William R. Cook, editors, *OOPSLA Companion*, pages 719–720. ACM, 2006. ISBN 1-59593-491-X.
- C. Marshall. *Enterprise Modeling with UML. Designing Successful Software Through Business Analysis*. Addison Wesley, 2000. ISBN 0201433133.
- OMG. *Object Constraint Language 2.0*. Object Management Group, formal/06-05-01 edition, 2006. URL http://www.omg.org/technology/documents/modeling_spec_catalog.htm.
- OMG. *MDA Guide Version 1.0.1*. Object Management Group, document number: omg/2003-06-01 edition, June 2003. URL <http://www.omg.org/mda>.
- OMG. *Unified Modeling Language: Superstructure, version 2.1.1*. Object Management Group, version 2.1.1 formal/2007-02-05 edition, February 2007. URL http://www.omg.org/technology/documents/modeling_spec_catalog.htm.
- F. B. Vernadat. *Enterprise Modeling and Integration: Principles and Applications*. Chapman and Hall, 1996. ISBN 0412605503.
- T. J. Williams. The Purdue Enterprise Reference Architecture. In *Proceedings of the Workshop on Design of Information Infrastructure Systems for Manufacturing*. Elsevier, November 1993. URL http://www.ecn.purdue.edu/IIES/PLAIC/Enterprise-Handbook_PERA.pdf.