

LIST OF FIGURES

No.	Title	Page
1.1	Control system design methodology	2
1.2	General refrigeration cycle	5
2.1	Relationship between pole position and transient response	33
3.1	Two-stage refrigeration system	43
3.2	General Evaporator	45
3.3	Condenser and receiver	49
3.4	General compressor and inter-mixing node	52
3.5	Comparison between actual data and fitted curve for Equation 3.21 for the first compressor	58
3.6	Comparison between actual data and fitted curve for Equation 3.21 for the second compressor	59
3.7	Comparison between actual data and fitted curve for Equation 3.23 for the first compressor	60
3.8	Comparison between actual data and fitted curve for Equation 3.23 for the second compressor	61
4.1	Outline of explicitly structured programs in ACSL	65
4.2	System matrices	71
4.3	Validation of the linearised model	73
5.1	Conventional Control Approach	77
5.2	Direct Temperature Control Approach	78
5.3	Cascade Temperature Control Approach	79
5.4	Cascade Liquid Flow Case (C/Liq)	80
5.5	Cascade Vapour Flow Case (C/Vap)	81

5.6	Case L1/L3	81
5.7	Case L2/L3	82
5.8	Root locus plots for the candidate control loops	87
5.9	Example of obtaining tuning parameters based on optimising individual control loops (P1-N loop)	88
5.10	Loops Tuning based on optimisation of ISE of TP1o	89
5.11	Effect of changing the gain of L1 loop on the ISE of L1 and TP1o	90
5.12	Variation of ISE of each control loop as a result of changing the TP1o gain factor	90
5.13	Performance of the two-stage refrigeration system with the conventional approach using dominant pole tuning and Dacey's tuning	95
5.14	Performance of the two-stage refrigeration system comparing the conventional, cascade temperature and direct temperature control approaches	96
5.15	Performance of the two-stage refrigeration system with the cascade temperature control approach using Base 5-loop Case and cascade liquid flowrates	99
5.16	Performance of the two-stage refrigeration system with the cascade temperature control approach, but with a reduced number of control loops	104
5.17	Performance of the two-stage refrigeration system with the cascade temperature control approach with positive and negative step change of 2 K in TP1i	106
5.18	Performance of the two-stage refrigeration system with the cascade temperature control approach with disturbances in TP1i and TP2i	107
5.19	Performance of the two-stage refrigeration system with the cascade temperature control approach with disturbances in TP1i and TP3i	108
5.20	Non-linear effects in the two-stage refrigeration system with the cascade temperature control approach with positive and negative	109

	step change of 2 K in TP1i, gain factor on TP1o-P1 loop = 0.02	
6.1	Results of controllability analysis using the condition number - (for Cases 1-7 defined in Table 6.1)	118
6.2	Results of controllability analysis using the minimised condition number - (for Cases 1-7 defined in Table 6.1)	119
6.3	Results of resiliency analysis using the minimum singular values - (for Cases 1-7 defined in Table 6.1)	121
6.4	DIM analysis results - (for Cases 1-7 defined in Table 6.1)	130
6.5	PIM analysis results - (for Cases 1-7 defined in Table 6.1)	131
6.6	μ IM analysis results - (for Cases 1-7 defined in Table 6.1)	132
7.1	Steady state SFG for the 2×2 system defined in Equation 7.1	139
7.2	SFG for the 2×2 system –transfer function representation for the pairing x_1-u_1 & x_2-u_2	140
7.3	Stability of closed loop system for the pairing x_1-u_1 & x_2-u_2 when both loops are closed	142
7.4	Responses of x_1 and x_2 to unit changes in their set point (x_1-u_1 & x_2-u_2 pairings). Interaction between the loops ensures stability so long as both loops are closed	143
7.5	SFG for the 2×2 system –transfer function representation for the pairing x_1-u_2 & x_2-u_1	144
7.6	Stability of closed loop system for the pairing x_1-u_2 & x_2-u_1 when both loops are closed	145
7.7	Responses of x_1 and x_2 to unit changes in their set point (x_1-u_2 & x_2-u_1 pairings). Interaction between the loops shows instability so long as both loops are closed	146
7.8	Responses of x_1 and x_2 to unit changes in their set point (x_1-u_1 & x_2-u_2 pairings) illustrating interaction in the system	153
7.9	Control scheme of the gasifier	160